

Specification

Nominal Voltage	6V	
Nominal Capacity(20HR)	13.0AH	
Dimensions	Length	108±2mm (4.25 inches)
	Width	70±1mm (2.76 inches)
	Container Height	140±2mm (5.51 inches)
	Total Height (with Terminal)	140±2mm (5.51 inches)
	Approx Weight	Approx 2.24 kg (4.94lbs)
Terminal	NT1 / PT2	
Container Material	ABS	
Rated Capacity	13.0 AH/0.650A	(20hr, 1.80V/cell, 25°C/77°F)
	12.09 AH/1.21A	(10hr, 1.80V/cell, 25°C/77°F)
	11.05 AH/2.21A	(5hr, 1.75V/cell, 25°C/77°F)
	9.96 AH/3.32A	(3hr, 1.75V/cell, 25°C/77°F)
	8.16 AH/8.16A	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	195A (5s)	
Internal Resistance	Approx 12mΩ	
Operating Temp. Range	Discharge	-15~50°C (5~122°F)
	Charge	0~40°C (32~104°F)
	Storage	-15~40°C (5~104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 3.9A. Voltage	
	7.2V~7.5V at 25°C(77°F)Temp. Coefficient -15mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	6.75V~6.9V at 25°C(77°F)Temp. Coefficient -10mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Leoch LP series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	24.8	19.0	15.7	13.6	10.5	7.76	6.54	3.87	3.03	2.46	2.01	1.74	1.40	1.17	0.644
1.80V/cell	33.2	24.3	19.0	16.1	12.4	9.02	7.32	4.22	3.26	2.63	2.15	1.87	1.49	1.21	0.650
1.75V/cell	37.5	26.7	20.8	17.3	12.9	9.36	7.66	4.38	3.32	2.68	2.21	1.92	1.51	1.24	0.657
1.70V/cell	41.3	29.1	22.2	18.2	13.4	9.73	7.90	4.49	3.41	2.76	2.27	1.96	1.54	1.27	0.668
1.65V/cell	45.5	31.4	23.6	19.3	14.2	9.98	8.09	4.55	3.55	2.85	2.33	2.00	1.56	1.29	0.677
1.60V/cell	50.2	34.1	25.2	20.6	15.0	10.4	8.16	4.75	3.66	2.94	2.41	2.04	1.58	1.31	0.681



Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	45.3	35.1	29.4	25.7	20.1	14.9	12.6	7.51	5.90	4.81	3.93	3.42	2.77	2.32	1.27
1.80V/cell	60.1	44.3	35.0	29.9	23.3	17.2	14.0	8.14	6.31	5.11	4.20	3.66	2.93	2.39	1.29
1.75V/cell	66.3	47.9	37.8	31.9	24.0	17.7	14.6	8.41	6.40	5.20	4.30	3.74	2.97	2.45	1.30
1.70V/cell	71.0	51.1	39.8	33.2	24.8	18.3	15.0	8.60	6.57	5.33	4.40	3.82	3.01	2.50	1.32
1.65V/cell	77.2	54.6	42.0	35.0	26.0	18.6	15.3	8.68	6.82	5.49	4.50	3.89	3.05	2.54	1.34
1.60V/cell	83.2	57.9	44.2	36.9	27.3	19.3	15.3	9.00	6.99	5.65	4.64	3.96	3.08	2.57	1.35


Dimensions

NT1/PT2 Terminal


Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



Sales Office

China sales office:

Add: 5th Floor, Xinbaohui Bldg., Nanhai Blvd.,
Nanshan, Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail: export@leoch.com
Http://www.leoch.com

North America sales office:

Add: 19751 Descartes, Unit A,
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

Europe sales office:

Add: 9B Wheatstone Park, Waterwells
Business Park, Gloucester, GL2 2AQ, UK.
Tel: +44(0) 01452 729428
Fax: +44 (0)1452-690125
E-mail: Sales.Europe@leoch.com

Singapore sales office:

Add: No. 53, Ubi Avenue 1, #03-21 Paya
Ubi Industrial Park, Singapore 408934
Tel: + 65 6841 6629
E-mail: sales.sg@leoch.com

HongKong sales office:

Add: Unit 3910, 39/F, Cable TV Tower, No. 9
Hoi Shing Road, Tsuen Wan, NT, H.K
Tel: +852 3578 6666
E-mail: sales.hk@leoch.com